

Easy Change new STRONG version



To meet the demands of a compact change machine with unbeatable security

The most copied changemachine in the range has been updated in terms of design and construction materials to ensure unbeatable security.

Easy Change integrates itself well into any everyday scene; a shopping centre, a gym, an airport or train station, an amusement arcade, an office or an internet café.

Two cross-beams forged from special iron protect the machine from any attempt of breaking in.

These bars are held in place by means of two suitable holes, and can be secured by external padlocks.

The special lid of the hopper extension stops any money falling out if the unit is tipped up.

All takings are further protected by the Locky System anti-theft device.

While maintaining its small dimensions, Easy Change boasts a huge coin capacity thanks to the extension to the hopper.

Easy Change is also available with a "Multicoin" hopper to dispense simultaneously 3 different types of coin.

Easy wall-mountable thanks to the Easy UP kit.

Also available with a special kit for the reinforcement of changemachines already in use.





Fig. 1



Fig. 2



Fig. 3



Fig. 4

General characteristics

An exceptionally robust structure strengthened closing mechanism, new anti-theft and anti-drilling protection. All these features ensure EasyChange is one of the most secure machines on the market.

Two cross-beams forged from special iron protect the machine from any attempt of breaking in. These bars are held in place by means of two suitable holes, and can be secured by external padlocks which are available upon request (Fig. 1).

The special lid of the hopper extension stops any money falling out if the unit is tipped up (Fig. 2).

The casing of the changemachine has fixing holes for other machines or external structures such as a pillar or column.

Switching on or off of the machine is possible only from inside the machine itself, to avoid tampering.

The tilting door renders replenishing the hopper and money extraction jobs easier.

Installation

Installation can be carried out:

- On the wall, via 3 wall plugs inserted into the rear of the unit.
- On the wall, using the Easy-UP kit (Fig. 3).
- On a resting bench;
- On the floor, using an optional stand.

Electronic characteristics

Available in many versions furnished with:

- RM5 Evolution electronic coin-validator;
- NV10 or EBA 03 banknote reader;
- NV9 banknote reader with stacker;
- 16 character, 2 line LCD display (as standard);
- CPU card with data sampling of takings (as standard);
- Evolution hopper with extension (as standard);
- Discriminator hopper and NV9 banknote reader with stacker.

Options

- Support stand;
- Easy UP installation kit;
- Locky System anti-theft device for changemachines (Fig. 4);
- Reprogrammable locking.

Technical characteristics

	Change machine	Change machine on support stand
Dimensions (bxhxp) (mm)	257 x 473 x 353	257 x 1.430 x 353
Weight (Kg)	25	38
Input voltage	230 Vac - 50 Hz	
Current used	0,261 A	
Power used	60 W max	
Operating temperature	0°C ÷ +50°C	

Coin capacity

	0,50 €	1,00 €	2,00 €
1 Evolution with extension	2.400	2.400	2.200
1 Discriminator with extension	4.000	3.800	3.500

Tools

Programmer
Standard.

